



600PSI

19	Adapter	20000372	2	ABS	
18	O-Ring	20000322	4	EPDM	17*2.65
17	Screw	20000211	2	304SST	M6*20
16	Saddle	20000003	2~3	Rubber	
15	Strap Screw	20000200	4~6	304SST	M8*70
14	Strap	20000191	2~3	304SST-Rubber	
13	O-Ring	20000325	4	EPDM	25*2.65
12	Securing Screw	20000205	6	304SST	M6*10
11	Plug	20000078	1	ABS	
10	Permeate Port	20000080	2	ABS	
9	Locking Kit Segment	20000013 14 15	6	316SST	
8	O-Ring	20000320	4	EPDM	19*2.65
7	Bearing Plate	20000409	2	Aluminium Alloy	
6	Feed/Conc. Port	20000492	2~4	2205SST/2507SST	
5	Retaining Ring	20000019	2~4	304SST	
4	O-Ring	20000326	4~8	EPDM	28*2.65
3	O-Ring	20000319	4	EPDM	90*5.3
2	Sealing Plate	20000286	2	ABS	
1	Pressure Shell	See SelectionTable	1	Epoxy FRP	White
Ref.	Description	Part Number	Qty.	Material	Remark

Note

1. Design pressure: 600PSI (41Bar)
2. Design temperature: 150° F (66° C)
3. Minimum temperature: 14° F (-10° C)
4. Working medium: Water, PH 3-11
5. Please operate in accordance with User Guide
6. Flexible piping should be used on permeate connection to mainfold
7. Side port misalignment can not exceed 0.7mm in any direction
8. Subject to change without prior notice

Ref.	Part Number	L (MM)	P (MM)	S (MM)	Approx assembly weight (KG)
1	F40600S-1	1364	1036	600	11
2	F40600S-2	2380	2052	1200	15
3	F40600S-3	3396	3068	2200	19
4	F40600S-4	4412	4084	1600x2	22
5	F40600S-5	5428	5100	2300x2	26
6	F40600S-6	6444	6116	2700x2	30

Harbin FirstLine Environment Technology Co., Ltd.

First Line	Design	Model
	Date	
	Review	F40-600S Pressure Vessel
	Date	
	Review	
Date	DRG	
Review		
Date	F40-60-S-00-01	
Review		
Date		
Approval	Unit	REV.
Date	mm	2023